



通径DN	结构长度L		PN0.6MPa			PN1.0MPa			PN1.6MPa		
	短	长	D	D1	Z-d	D	D1	Z-d	D	D1	Z-d
40	106	140	130	100	4-11	150	110	4-18	150	110	8-18
50	108	150	140	110	4-11	165	125	4-18	165	125	8-18
65	112	170	160	130	4-11	185	145	8-18	185	145	8-18
80	114	180	190	150	4-18	200	160	8-18	200	160	8-18
100	127	190	210	170	4-18	220	180	8-18	220	180	8-18
125	140	200	240	200	4-18	250	210	8-18	250	210	8-18
150	140	210	265	225	8-18	285	240	8-22	285	240	8-22
200	152	230	320	280	8-18	340	295	8-22	340	295	12-22
250	165	250	375	335	12-18	395	350	12-22	405	355	12-26
300	178	270	440	395	12-22	445	400	12-22	460	410	12-26
350	190	290	490	445	12-22	505	460	16-22	520	470	16-26
400	216	310	540	495	16-22	565	515	16-26	580	525	16-30
450	222	330	595	550	16-22	615	565	20-26	640	585	20-30
500	229	350	645	600	20-22	670	620	20-26	715	650	20-33
600	267	390	755	705	20-26	780	725	20-30	840	770	20-36
700	292	430	860	810	24-26	895	840	24-30	910	840	24-36
800	318	470	975	920	24-30	1015	950	24-33	1025	950	24-39
900	330	510	1075	1020	24-30	1115	1050	28-33	1125	1050	28-39
1000	410	550	1175	1120	28-30	1230	1160	28-36	1255	1170	28-42
1200	470	630	1405	1340	32-33	1455	1380	32-39	1485	1390	32-48
1400	530	710	1630	1560	36-36	1675	1590	36-42	1685	1590	36-48
1600	600	790	1830	1760	40-36	1915	1820	40-48	1930	1820	40-56
1800	670	870	2045	1970	44-39	2115	2020	44-48	2130	2020	44-56
2000	760	950	2265	2180	48-42	2325	2230	48-48	2345	2230	48-62

通径DN	结构长度L		PN2.5MPa			PN4.0MPa		
	短	长	D	D1	Z-d	D	D1	Z-d
40	106	140	150	110	4-18	150	110	4-18
50	108	150	165	125	4-18	165	125	4-18
65	112	170	185	145	8-18	185	145	8-18
80	114	180	200	160	8-18	200	160	8-18
100	127	190	235	190	8-22	235	190	8-22
125	140	200	270	220	8-26	270	220	8-26
150	140	210	300	250	8-26	300	250	8-26
200	152	230	360	310	12-26	375	320	12-30
250	165	250	425	370	12-30	450	385	12-33
300	178	270	485	430	16-30	515	450	16-33
350	190	290	555	490	16-33	580	510	16-36
400	216	310	620	550	16-36	660	585	16-39
450	222	330	670	600	20-36	685	610	20-39
500	229	350	730	660	20-36	755	670	20-42
600	267	390	845	770	20-39	890	795	20-48
700	292	430	960	875	24-42	—	—	—
800	318	470	1085	990	24-48	—	—	—
900	330	510	1185	1090	28-48	—	—	—
1000	410	550	1320	1210	28-56	—	—	—
1200	470	630	1530	1420	32-56	—	—	—
1400	530	710	1755	1640	36-62	—	—	—
1600	600	790	1975	1860	40-62	—	—	—
1800	670	870	2195	2070	44-70	—	—	—
2000	760	950	2425	2300	48-70	—	—	—

注：D—法兰外圆 D1—法兰中心距 Z-d— 法兰孔数-孔径